



## Features

- Industry standard small form pluggable (SFP) package
- Duplex LC connector
- Hot Pluggable
- Single power supply 3.3V
- Operating Temp. -40°C to 85 °C ( Others ) and -20°C to 85 °C( 7350-162 )
- Storage Temp. -40° to 85°C
- Wave-length : By model
- TTL signal detect indicator
- Differential LVPECL inputs and outputs
- Class 1 laser product complies with EN 60825-1
- Compliant with Fiber Channel 100-M5-SN-I and 100-M6-SN-I standard
- Compliant with IEEE802.3z Gigabit Ethernet standard

## Application

- Distributed Multi-processing
- Switch to switch interface
- High speed I/O for file server
- Bus extension application

## Ordering information

<b>7350-162</b> .....	<b>P/N: 7350-162</b>
1.25G b SFP, Multi-Mode, 850nm, LC, -20C~85C (mini-GBIC-SX/550m) 1000 Base	
<b>7350-163</b> .....	<b>P/N: 7350-163</b>
1.25G b SFP, Multi-Mode, 1310nm , LC, -40C~85C, (mini-GBIC-SX+/2km), 1000Base	
<b>7350-165</b> .....	<b>P/N: 7350-165</b>
1.25G b SFP, Single-Mode, 1310nm, LC, -40C~85C (Mini-GBIC-LX/10km), 1000Base-LX	
<b>7350-168</b> .....	<b>P/N: 7350-168</b>
1.25G b SFP, Single-Mode, 1310nm, LC, -40C~85C (Mini-GBIC-LX/20km), 1000Base-LX	
<b>7350-164</b> .....	<b>P/N: 7350-164</b>
1.25G b SFP, Single-Mode, 1310nm, LC, -40C~85C (mini-GBIC-LHX/30~40km)	
<b>7350-166</b> .....	<b>P/N: 7350-166</b>
1.25G b SFP, Single-Mode, 1550nm, LC, -40C~85C (mini-GBIC-XD/50km), 1000Base	
<b>7350-167</b> .....	<b>P/N: 7350-167</b>
1.25G b SFP, Single-Mode, 1550nm, LC, -40°C~85°C (mini GBIC-/ZX/70Km) 1000Base	
<b>7350-175</b> .....	<b>P/N: 7350-167</b>
1.25G b SFP, Single-Mode, 1550nm, LC, -40°C~85°C (mini GBIC-/ZX/70Km) 1000Base	
<b>7350-176</b> .....	<b>P/N: 7350-176</b>
1.25Gb SFP-BIDI Single-mode 10Km, TX1310/RX1490, -40°C~85°C , 1000Base-BX10-U	
<b>7350-177</b> .....	<b>P/N: 7350-177</b>
1.25Gb SFP-BIDI Single-mode 10Km, TX1490/RX1310, -40°C~85°C , 1000Base-BX10-D	