



## Features

- Industry standard small form pluggable (SFP) package
- Duplex LC connector
- Hot Pluggable
- Single power supply 3.3V
- Operating Temp. 0°C to 70 °C
- Storage Temp. -40° to 85°C
- Wave-length : By model
- TTL signal detect indicator
- Differential LVPECL inputs and outputs
- Class 1 laser product complies with EN 60825-1

## Application

- Distributed Multi-Processing
- Switch to switch interface
- High speed I/O for file server
- Bus extension application
- Channel extender, data storage

## Ordering information

<b>7330-062</b> .....	<b>P/N: 7330-062</b>
155Mbps SFP, Multi-mode, 850nm, LC, 0C~70C( min-GBIC-2km)	
<b>7330-063</b> .....	<b>P/N: 7330-063</b>
155Mbps SFP, Multi-mode, 1310nm, LC, 0C~70C( min-GBIC-2km)	
<b>7330-064</b> .....	<b>P/N: 7330-064</b>
155Mbps SFP, Single-mode, 1310nm, LC, 0C~70C( min-GBIC-30km)	
<b>7330-065</b> .....	<b>P/N: 7330-065</b>
155Mbps SFP, Single-mode, 1310nm, LC, 0C~70C( min-GBIC-60km)	
<b>7330-066</b> .....	<b>P/N: 7330-066</b>
155Mbps SFP, Single-mode, 1550nm, LC, 0C~70C( min-GBIC-100km)	
<b>7330-067</b> .....	<b>P/N: 7330-067</b>
155Mbps SFP, Single-mode, 1550nm, LC, 0C~70C( min-GBIC-120km)	
<b>7330-075</b> .....	<b>P/N: 7330-075</b>
155Mbps SFP-BIDI, Single-mode, TX 1310/RX 1490nm, LC, 0C~70C	
<b>7330-076</b> .....	<b>P/N: 7330-076</b>
155Mbps SFP-BIDI, Single-mode, TX 1490/RX 1310nm, LC, 0C~70C	