



Features

- Industry standard small form pluggable (SFP) package
- Duplex LC connector
- Hot Pluggable
- Single power supply 3.3V
- Operating Temp. 0°C to 70 °C
- Storage Temp. -40° to 85°C
- Wave-length : By model
- TTL signal detect indicator
- Differential LVPECL inputs and outputs
- Class 1 laser product complies with EN 60825-1
- Compliant with Fiber Channel 100-M5-SN-I and 100-M6-SN-I standard
- Compliant with IEEE802.3z Gigabit Ethernet standard

Application

- Distributed Multi-Processing
- Switch to switch interface
- High speed I/O for file server
- Bus extension application
- Channel extender, data storage

Ordering information

7330-162	P/N: 7330-162
1.25Gb SFP, Multi-Mode, 850nm, LC, 0C~70C (mini-GBIC-SX/550m), 1000Base-SX		
7330-163	P/N: 7330-163
1.25Gb SFP, Multi-Mode, 1310nm, LC, 0C~70C (mini-GBIC/2km), 1000Base-SX+		
7330-165	P/N: 7330-165
1.25Gb SFP, Single-Mode, 1310nm, LC, 0C~70C (mini-GBIC-LX/10km), 1000Base-LX		
7330-164	P/N: 7330-164
1.25Gb SFP, Single-Mode, 1310nm, LC, 0C~70C (mini-GBIC-LHX/30~40km)		
7330-166	P/N: 7330-166
1.25Gb SFP, Single-Mode, 1550nm, LC, 0C~70C (mini-GBIC-XD/50km), 1000Base		
7330-167	P/N: 7330-167
1.25Gb SFP, Single-Mode, 1550nm, LC, 0°C~70°C (mini GBIC-/ZX/70Km) 1000Base		
7330-175	P/N: 7330-175
1.25Gb SFP, BIDI Single-Mode, 1550nm, LC, 0°C~70°C (mini GBIC-/EZ/110Km)		
7330-176	P/N: 7330-176
1.25Gb SFP-BIDI Single-mode 10Km, TX1310/RX1490, 0°C~70°C , 1000Base-BX10-U		
7330-177	P/N: 7330-177
1.25Gb SFP-BIDI Single-mode 10Km, TX1310/RX1490, 0°C~70°C , 1000Base-BX10-U		