



- **Metal Case with Palm Size**
- **Auto-MDI/MDI-X**
- **Auto-Negotiation**
- **Non-Blocking**
- **Store and Forward**
- **Smart Plug and Play**

Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.ab 1000BaseT

IEEE 802.3z 1000BaseSX/LX

IEEE 802.3x Full-duplex and Flow Control

Number of Port

4-port 10/100BaseT(X)+1-port 100BaseFX

Mechanical:

LED Indicator

Per Port: Link / Act

Per Unit: Power

Power Consumption

3 Watts (Max)

Power Supply

DC 5V~12V

Product Dimensions / Weight

130 x 77 x 24 mm (L x W x H)/ 0.28 kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class B, CE

Performance:

MAC Address: 1K

Buffer Memory: 384K bits

Transmission Method: Store and Forward

Package information:

Accessory

Power Adapter

User Manual

Rubber footpad

Color Box Dimension

191x 116 x 90 mm (L x W x H)

Carton Dimension

506x 400x 261 mm ; 20 pcs/ per carton

N.W / G.W

15.6 kg / 16.6 kg