



- **Metal Case with Palm Size**
- **Auto-MDI/MDI-X**
- **Auto-Negotiation**
- **Non-Blocking**

## Specifications:

### Standard

IEEE 802.3 10BaseT  
IEEE 802.3u 100BaseFX  
IEEE 802.3u 100BaseTX  
IEEE 802.3x Flow Control

### Number of Port

7-port 10/100BaseT(X)+1-port 100BaseFX

### Mechanical:

#### LED Indicator

Per Port: Link / Act  
Per Unit: Power

#### Power Consumption

5 Watts (Max)

#### Power Supply

DC 5V~12V

#### Product Dimensions / Weight

130 x 77 x 24 mm (L x W x H)/ 0.32 kg

#### Environmental Specification:

##### Operating Temperature

0 to 45 °C

##### Storage Temperature

-20 to 90 °C

##### Humidity

10 to 90% RH (non-condensing)

#### Certification

FCC Class B, CE

## Performance:

MAC Address: 1K

Buffer Memory: 768K bits

Transmission Method: Store and Forward

## Package information:

### Accessory

Power Adapter

User Manual

Rubber footpad

### Color Box Dimension

191x 116 x 90 mm (L x W x H)

### Carton Dimension

506x 400x 261 mm ; 20 pcs/ per carton

### N.W / G.W

15.6 kg / 16.6 kg