



Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.3u 100BaseFX

IEEE 802.3x Full-duplex and Flow Control

IEEE 802.1p QoS

IEEE 802.1Q VLAN

Number of Port

6-port 10/100BaseT(X)+ 2-port 100BaseFX

Mechanical:

LED Indicator

Per Port: Link / Act

Per Unit: Power

Power Consumption

5 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

228X 124X 44mm (L x W x H)/ 1.05kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class A, CE

- Web-based Configuration and Management

- 9" Metal Case

- Rack-Mount to 10" / 19" Cabinet

- No Fan No Noise

- Internal Power Supply

Web Management Feature:

Port Management:

Port Configuration

Bandwidth Control

Broadcast Storm Control

VLAN Setting:

Port-based / Tag-based

QoS Setting

Port Security Setting

Performance:

MAC Address: 1K

Buffer Memory: 512K bits

Transmission Method: Store and Forward

Package information:

Accessory

Power Cord

User Manual

Rack-mount kit (Optional)

Color Box Dimension

295X 240X 65 mm (L x W x H)

Carton Dimension

618x 370x 258 mm ; 10 pcs/ per carton

N.W / G.W

15.8kg / 16.8kg