

BES-516W 16-port 10/100TX Web-Managed Switch



Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.3x Full-duplex and Flow Control

IEEE 802.1Q VLAN

IEEE 802.1p QoS

Number of Port

16-port 10/100BaseT(X)

Mechanical:

LED Indicator

Per Port: Link / Act, 10/100M

Per Unit: Power

Power Consumption

5 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

266X 160X 44mm (L x W x H)/ 1.33kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class A, CE

- **Web-based Configuration and Management**
- **11" Metal Case and Rack-Mount to 19" Cabinet**
- **No Fan, No Noise**
- **Internal Power Supply**

Web Management Feature:

Port Management:

Port Configuration

Port Mirroring

Bandwidth Control

Broadcast Storm Control

VLAN Setting:

Port-based / Tag-based

Trunking:

2 groups per device, 4 ports per group

QoS Setting

Security Setting

MAC address filtering

TCP/UDP Port filtering

IGMP Snooping

Backup/ Recovery Configuration

Performance:

MAC Address: 4K

Buffer Memory: 1.625Mb

Transmission Method: Store and Forward

Performance:

Package information:

Accessory and Power Cord

User Manual

Rack-mount kit (Optional)

Color Box Dimension

295X 240X 65 mm (L x W x H)

Carton Dimension

618x 370x 258 mm ; 10 pcs/ per carton