

BES-716 16-port 10M / 100M Rack-mount Fast Ethernet Switch

LCSI



- 19" Industrial Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Internal Power Supply

Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.3x Full-duplex and Flow Control

Number of Port

16-port 10/100BaseT(X)

Mechanical:

LED Indicator

Per Port: Link/Act, 10/100M

Per Unit: Power

Power Consumption

7.5 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 2.5kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class A, CE

Performance:

MAC Address: 4K

Buffer Memory: 1.625M bits

Transmission Method: Store and Forward

Package information:

Accessory

Power Cord

User Manual

Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397mm ; 4 pcs/per carton

N.W / G.W

12.7 kg / 13.8 kg