

BES-7242 24-port 10/ 100M + 2 Combo Gigabit Copper/SFP Switch



Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.ab 1000BaseT

IEEE 802.3z 1000BaseSX/LX

IEEE 802.3x Full-duplex and Flow Control

Number of Port

24-port 10/100T(X) +

2 Combo Gigabit UTP port/SFP Open Slots

Mechanical:

LED Indicator

Per Port: Link / Act, 10/100M (port1~24)

Per Port: Link / Act, 1000M (port25~26)

Per Unit: Power

Power Consumption

12.5 Watts (Max)

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 3.1kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class A, CE

- 19" Industrial Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking and Store and Forward
- Internal Power Supply

Performance:

MAC Address: 4K

Buffer Memory: 2.75Mb

Transmission Method: Store and Forward

Package information:

Accessory

Power Cord

User Manual

Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397mm : 4 pcs/per carton

N.W / G.W

14.2 kg / 15.2 kg