



### Specifications:

#### Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.3x Full-duplex and Flow Control

#### Number of Port

48-port 10/100BaseT(X)

#### Mechanical:

##### LED Indicator

Per Port: Link / Act, 10/100M

Per Unit: Power

##### Power Consumption

15 Watts (Max)

##### Power Supply

100~240V/AC, 50~60Hz

##### Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 3.2kg

#### Environmental Specification:

##### Operating Temperature

0 to 45 °C

##### Storage Temperature

-20 to 90 °C

##### Humidity

10 to 90% RH (non-condensing)

#### Certification

FCC Class A, CE

- 19" Industrial Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Internal Power Supply

### Performance:

MAC Address: 8K

Buffer Memory: 2.5Mb

Transmission Method: Store and Forward

### Package information:

#### Accessory

Power Cord

User Manual

Rack-mount kit

#### Color Box Dimension

500 x 360 x 91 mm (L x W x H)

#### Carton Dimension

524 x 327 x 397mm ; 4 pcs / per carton

#### N.W / G.W

15 kg / 16 kg