



- Metal Case with Palm Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Store and Forward
- Smart Plug and Play

Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.3ab 1000BaseT

IEEE 802.3z 1000BaseSX/LX

IEEE 802.3x Full-duplex and Flow Control

Number of Port

4-port 10/100/1000BaseT(X)+1-port 1000BaseSX/LX

Mechanical:

LED Indicator

Per Port: Link / Act

Per Unit: Power

Power Consumption

6 Watts (Max)

Power Supply

DC 5V~12V

Product Dimensions / Weight

Environmental Specification:

Operating Temperature

Storage Temperature

Humidity

Certification

Performance:

MAC Address: 1K

Buffer Memory: 832K bits

Transmission Method: Store and Forward

Package information:

Accessory

Power Adapter

User Manual

Rubber footpad

Color Box Dimension

191x 116 x 90 mm (L x W x H)

Carton Dimension

506x 400x 261 mm ; 20 pcs/ per carton

N.W / G.W

15.6 kg / 16.6 kg

130 x 77 x 24 mm (L x W x H)/ 0.28 kg

0 to 45 °C

-20 to 90 °C

10 to 90% RH (non-condensing)

FCC Class B, CE