



Specifications:

Standard

IEEE 802.3 10BaseT
IEEE 802.3u 100BaseTX
IEEE 802.3ab 1000BaseT
IEEE 802.3z 1000BaseSX/LX
IEEE 802.3x Full-duplex and Flow Control

Number of Port

16-port 10/100/1000BaseT(X) +
4 Gigabit SFP Open Slots

Mechanical:

LED Indicator

Per Port: Link / Act, 1000M
Per Unit: Power

Power Consumption

15 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 2.6 kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class B, CE

- 19" Industrial Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking

Performance:

MAC Address: 8K
Buffer Memory: 340K Bytes
Jumbo Frames: 9.6K
Transmission Method: Store and Forward

Package information:

Accessory

Power Cord
User Manual
Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397mm ; 4 pcs/per carton

N.W / G.W

13.9 kg / 14.9 kg