



Specifications:

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.ab 1000BaseT

IEEE 802.3z 1000BaseSX/LX

IEEE 802.3x Full-duplex and Flow Control

IEEE 802.1x PNAC

(Port-based Network Access Control)

IEEE 802.1Q VLAN

IEEE 802.3ad Link Aggregation

IEEE 802.1d STP

IEEE 802.1w RSTP

IEEE 802.1p CoS, Priority Protocols

Number of Port

16-port 10/100/1000BaseT(X) +

4 Gigabit SFP Open Slots

Mechanical:

LED Indicator

Per Port: Link / Act, 1000M

Per Unit: Power

Power Consumption

15 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 3kg

Environmental Specification:

Operating Temperature

Storage Temperature

Humidity

Certification

• IEEE 802.1Q VLAN, 802.1p Priority Queues

• Jumbo Frames and IGMP Support

• Link Aggregation and RSTP, SNMP Support

Web Management Feature:

VLAN : Port-based/ Tag-based VLAN

VLAN ID: 1~4094

Link Aggregation (Trunk)

RSTP

IGMP Snooping

QoS

IP Filtering

Rate Limiting Control

Storm Control

Port Mirroring

Management:

Password-protected Access, Port Setting

Performance:

MAC Address: 8K

Buffer Memory: 340K Bytes

Jumbo Frames: 9.6K

Transmission Method: Store and Forward

Package information:

Accessory: Power Cord, User Manual

Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397mm ; 4 pcs/per carton

N.W / G.W: 13.9 kg / 14.9 kg

0 to 45 °C

-20 to 90 °C

10 to 90% RH (non-condensing)

FCC Class B, CE