



Specifications:

Standard

IEEE 802.3 10BaseT
 IEEE 802.3u 100BaseTX
 IEEE 802.ab 1000BaseT
 IEEE 802.3x Full-duplex and Flow Control
 IEEE 802.1x PNAC
 (Port-based Network Access Control)
 IEEE 802.1Q VLAN
 IEEE 802.3ad Link Aggregation
 IEEE 802.1d STP
 IEEE 802.1w RSTP
 IEEE 802.1p CoS , Priority Protocols

Number of Port

24-port 10/100/1000BaseT(X)

Mechanical:

LED Indicator

Per Port: Link / Act

Per Unit: Power

Power Consumption

20 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 3kg

Environmental Specification:

Operating Temperature

Storage Temperature

Humidity

Certification

- Web-based Configuration and Management
- IEEE 802.1Q VLAN Tagging
- 802.1p QoS, Priority Queues
- Jumbo Frame and IGMP Support, Lite-SNMP

Web Management Feature:

VLAN Setting:

Port-based/ Tag-based VLAN

VLAN ID: 1~4094

Link Aggregation (Trunk)

RSTP

IGMP Snooping

QoS

IP Filtering

Rate Limiting Control

Strom Control

Port Mirroring

Performance:

MAC Address: 8K

Buffer Memory: 500K Bytes

Jumbo Frames: 9.6K

Transmission Method: Store and Forward

Package information:

Accessory

Power Cord, User Manual Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397m m ; 4 pcs/per carton

N.W / G.W : 14.2 kg / 15.2 kg

0 to 45 °C

-20 to 90 °C

10 to 90% RH (non-condensing)

FCC Class A, CE