



Specifications:

Standard

IEEE 802.3 10BaseT

IEEE 802.3u 100BaseTX

IEEE 802.ab 1000BaseT

IEEE 802.3z 1000BaseSX/LX

IEEE 802.3x Full-duplex and Flow Control

Number of Port

24-port 10/100/1000BaseT(X) +

4 Combo Gigabit SFP Open Slots

Mechanical:

LED Indicator

Per Port: Link / Act, 1000M

Per Unit: Power

Power Consumption

20 Watts (Max)

Power Supply

100~240V/AC, 50~60Hz

Product Dimensions / Weight

440 x 220 x 44 mm (L x W x H) / 3.1kg

Environmental Specification:

Operating Temperature

0 to 45 °C

Storage Temperature

-20 to 90 °C

Humidity

10 to 90% RH (non-condensing)

Certification

FCC Class A, CE

- 19" Industrial Size
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Internal Power Supply

Performance:

MAC Address: 8K

Buffer Memory: 500K Bytes

Jumbo Frames: 9.6K

Transmission Method: Store and Forward

Package information:

Accessory

Power Cord

User Manual

Rack-mount kit

Color Box Dimension

500 x 360 x 91 mm (L x W x H)

Carton Dimension

524 x 327 x 397mm ; 4 pcs/per carton

N.W / G.W

14.1 kg / 15.1 kg