

CGC-U011SFP

10/100/1000BaseT to 1000SX/LX SFP Media Converter (standalone or housed in Chassis- BCR-16)



Highlights

- Complies with IEEE 802.3ab 1000BaseT and IEEE 802.3z 1000Base SX/LX Gigabit Ethernet standard
- SFP module slot supports either Multi-mode or Single-mode SFP module
- Compact size and easy to install.
- TP Port can support Full-Duplex, Auto-MDI/MDI-X and Auto-Negotiation
- Link Fault Pass through Function(DIP-Switch configurable)

Specification

Technology	
Standards	IEEE 802.3 10Base-T Ethernet
	IEEE 802.3u 100Base-TX/FX Fast Ethernet
	IEEE802.3xFlow Control and Back-pressure
	IEEE 802.3ab 1000Base T
	IEEE 802.3z 1000Base SX/LX
Processing Type	Store-and-Forward
Interface	
LED Indicators	Per unit: Power status ; Per Port: Link/Act
RJ45 Port	1 x 10/100/1000 BaseT, Auto MDI/MDIX
Fiber Port	1 x SFP module slot
Power	
Input	External adapter DC 5V/2A
Power Consumption	10W when operation at full load
Mechanical	
Casing	Metal Case
Dimensions	102mm(W)x74mm(D)x22mm(H)
Environment	
Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 90°C
Ambient Relative Humidity	10% to 90% (non-condensing)
Regulatory Approvals	
Safety	FCC Class A, CE

Ordering information

CGC-U011SFP
10/100/1000BaseT to 1000SX/LX SFP Media Converter (Standalone and housed in Chassis- BCR-16)
BCR-16
16 slots of Media Converter Chassis