

CMC-U011F-SC

10/100BaseTX to 100BaseFX Media Converter

Highlights



- Compact size and cost-effective
- Compliant with IEEE 802.3 10BaseT and IEEE 802.3u 100BaseTX/100BaseFX Standards
- One 100Base FX Fiber Port can support either Multi (SC/ST) or Single (SC) Mode
- 100 Base FX fiber port can support full/Half-duplex, Auto-negotiation, auto-MDI/MDIX
- LLF and LFP Functions

Specification

Technology	
Standards	IEEE 802.3 10Base-T Ethernet
	IEEE 802.3u 100Base-TX/FX Fast Ethernet
	IEEE 802.3x Flow Control
Processing Type	Store-and-Forward
Interface	
LED Indicators	Per unit: Power status Per Port: Link/Activity, Speed
RJ45 Port	1 x 10/100 Base-T(X), Auto MDI/MDIX
Fiber Port	1 x 100FX with Fiber connector Single/Multi-Mode, SC/ST/LC connector
Power	
Input	5 V DC Power input, 2A
Power Consumption	10W Max.
Mechanical	
Casing	Metal Case
Dimensions	102mm(W)x74mm(D)x22mm(H)
Weight	230g
Environment	
Operating Temperature	0 to 45
Storage Temperature	-20 to 90
Ambient Relative Humidity	10% to 90% (non-condensing)
Regulatory Approvals	
Safety	FCC Part 15, Class A, CE

Ordering information

CMC-U011F-SC /MM P/N: 4421-151
 10/100BaseTX to 100BaseFX Media Converter, Multi-mode fiber SC ,2Km Wavelength 1310
 CMC-U011F-SC /SM30 P/N: 4421-171
 10/100BaseTX to 100BaseFX Media Converter, Single-mode fiber SC ,30Km Wavelength 1310