

8-pair Port Desktop PoE Mid-span Power Supply



- * 8* 10/100BaseT(X) Data-In Ports + 8* 10/100BaseT(X) Data and Power-Out Ports
- * 11" Metal Case
- * Rack-Mount to 19" Cabinet
- * Internal Power Supply

BEP-508 is 8-pair Port Desktop Power over Ethernet Mid-span Power Supply that is designed for small or medium network environment to strengthen its network connection. This product is compact in size, making it ideal for Desktop users with limited space. It also gives you the option of installing it in a 19" cabinet by rack-mount kits or underneath a desk.

IEEE 802.3af Power over Ethernet (PoE) ports

BEP-508 features 8* 10/100BaseT(X) Data-In ports and 8* IEEE 802.3af Power over Ethernet (PoE) ports supplying up to 15.4 watts per port (Full Power). This product can convert standard 90~260V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3af compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3af compliant, or only the data will be sent through LAN cable. By adding BEP-508 to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

No Special Networking Cable Required

By adding PoE devices, you can use an existing standard Cat-5 Ethernet cable without a new electrical outlet for both power and data. It helps you reduce installation time and cost.

Standards	IEEE 802.3af IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX
Features	Number of Ports: 8 10/100BaseT(X) Data-In Ports 8 10/100BaseT(X) Data and Power-Out Ports
Led Indicators	Per Port: PoE Act/Status Per Unit: Power
Power Input	100~240V/AC, 50~60Hz
Power Output	48V/DC Per Port Output – 15.4 W Max Per Port 8 Ports at Full 15.4 W Output Supported
Power Consumption	120 Watts (Max)
Dimensions	266 x 160 x 44 mm (L x W x H)
Weight	1.9 kg
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class A, CE

Order Information

Model Name	Description
BEP-508	8-pair Port Desktop PoE Mid-span Power Supply, 11-inch metal case and rack-mountable